VZ-PRO-MX



Video Wall Controller


VZ-PRO-MX ADVANTAGES

- Support Max 3840 x 2160 @60 Hz
- Hot-Pluggable Structure and High Integration of Chassis
- Advanced Remote Control Software via TCP/IP
- Multiple Videowall Setting
- Built-in Matrix Function
- Synchronized Sub Monitor can be added

- Maximum Input and Outputs of 152 x 160
- Pure Hardware Structure, no Operating System and High Stability
- 19inch Rack Mount Capability
- Serial Control RS-232C Available
- Rack Moutable
- 3 year Warranty

VZ-PRO-MX Series is a FPGA-design professional high-performance image processing 4K video wall controller. It can display multiple images on multiple screens in real time without loss of frames for full function multi-window splicing. This advanced control device provides an ideal image processing solution for security operations centers, traffic control centers and other similar applications.

This wall controller adopts the large-scale high performance FPGA array and high–speed digital switching technology architecture and combined with full digital hardware design concept, provides a CPU-free operation and offers powerful processing capabilities such as broadband video signal acquisition and real-time high resolution digital image processing. VZ-PRO-MX uses digital multibus paralleling and digital multibus data switching processing mechanism that can fundamentally ensure all the input signal sources are processed with real-time processing and data consistency without delay, discretization and frame loss.




Z-PRO-MX



Video Wall Controller

	8RU	12RU	18RU	26RU	
	SPE	CIFICATIONS			
ame Number	VZ-	VZ-	VZ-	VZ-	
tal Card Support	20	40	60	80	
ax Input Card	18	38	38	76	
ax Output Card	10	20	20	40	
	RE	SOLUTION			
ax Resolution		3840 x 2160 @30Hz			
ax Bit Rate		25 Gbps per card			
pport Layers		Up to 4 layers for 4K (8 Layers for 2K) per output card			
ax Preset / Group		32 per group / 4			
	l l	NTERFACE			
out Card HDMI 4K Input Card (VZ-H4K	/I-IN1)	HDMI 2.0 - 1 Input I Up to 3840x2160/60p			
HDMI 4K Input Card (VZ-H4K	Λ-IN2)	HDMI 1.4 - 2 Inputs I Up to 3840x2160/30p			
HDMI HD Input Card (VZ-H2K	M-IN4)	HDMI 1.3 - 4 Inputs I Up to 1920x1080/60p			
DVI HD Input Card (VZ-D2KM	IN4)	DVI - 4 Inputs I Up to 1920x1080/60p			
SDI Input Card (VZ-S2KM-IN4		SDI - 2 Inputs I Up to 1920x1080/60p			
BNC Input Card (VZ-B1KM-IN	3)	BNC - 8 Inputs I CVBS			
IP Decoder Card (VZ-IPM-IN2	•	IP - 1 Input I H.265 IP Decorder - Decode up to 4 (4K) or 16 (1080p)			
itput Card HDMI 4K Output Card (VZ-H4		HDMI 2.0 - 1 Output I Up to 3840x2160/60p			
HDMI 4K Output Card (VZ-H4		HDMI 1.4 - 2 Outputs I Up to 3840x2160/30p			
HDMI HD Output Card (VZ-H2	•	HDMI 1.3 - 4 Outputs 1 Up to 1920x1080/60p			
DVI Output Card (VZ-D2KM-0	· ·	DVI - 4 Outputs I Up to 1920x1080/60p			
HDBase-T Output Card (VZ-H			· · · · · · · · · · · · · · · · · · ·		
nernet 10/100 (RJ45)	751-0014)	HDBase-T - 4 Outputs I Up to 1920zx1080/60p 1 (Remote Control)			
232 In / Out		1 (Serial Control/IR Receiver) / 1			
BB		For Firmware Update			
ib	WEIGHT	T & DIMENSIONS	mware opuate		
mensions (W x H x D)/ unit: inch	19 x 13.96 x 11.86	19 x 20.96 x 11.86	19 x 32.04 x 11.86	19 x 45.46 x 16	
mensions (W x H x D)/ unit: mm	482.52 x 354.75 x 301.4	482.52 x532.25 x 301.4	482.52 x 814 x 301.4	482.52 x 1154.85 x 406.4	
et Weight	39.6 lbs / 18kg	44 lbs / 20kg	55 lbs / 25kg	88 lbs / 40kg	
inch Rack Mount	2010 1107 2010	Support			
	REM	REMOTE CONTROL			
rial Control (RS232C) / Network		Yes (DB9 Connector) / TCP/IP (RJ45)			
mote Control Software for TCP/IP		Multiview Controller Software (Compatible with Windows XP/7/8/10)			
		GENERAL	, , , , ,		
wer Input		100 - 2	40V AC		
wer Consumption (Full load)	< 450 Watts	< 800 Watts	< 1000 Watts	< 2000 Watts	
dundant Power Supply			port		
perating Temperature		22~122°F/-5~50°C			
perating Humidity		5% - 95% Non-Condensing			
oling Fan		Support			
······ · · · · · · · · · · · · · · · ·		OPTION			
OMI Cable Extention Unit (VZ-1TRX-4K)			70m) / Requires DC5V power		
		Thou support up to 230166t	70111/7 Requires Des v power		

INTERFACE



- 1. External Input Sources HDMI, DVI, VGA, YPbPr, CVBS, SDI, DP, IP In
- 2. Output for Videowall Monitors 6. Ethernet 10/100 (RJ 45) HDMI, DVI, Fiber Optic Out
- 3. Status LED

- 4. RS232 In Serial Control / IR Receiver
- 5. RS 232 Out
- 7. Redundant AC 100-240V In


VZ-PRO-MX





12RU Chassis


26RU Chassis


Video Wall Controller













18RU Chassis





ViewZ and identifying product names and numbers herein are registered trademarks of ViewZ. All non-ViewZ brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status, and/or specifications are subject to change without notice.

Copyright © ViewZ. All rights reserved.

- * Availability of product may vary by country / region.
- * Product specifications in this brochure can change. Please confirm details on our website.

• Address: 177 W. Orangethorpe Ave., Placentia, CA 92870

• Phone: (714) 996-1177, Fax: (714) 996-1138

• Sales : sales@viewzusa.com

VZ-PRO-MX



Video Wall Controller

