

VZ-PVM-P1W3

SMART AD PVM w/CMS Software



VZ-PVM-P1W3 ADVANTAGES

- 13.3" Mega Pixel IP Full HD 1080p Resolution
- Onvif Profile S Compliant, NDA A Compliant
- Security Alert System
- Built-in Android OS w/CMS for Digital Signage
- Protective Glass / Camera Motion Sensor
- BNC(NTSC/PAL), RJ-45, Audio Out
- Camera Motion Sensor & Time Interval Based Source Switching
- Built-in 2 MP Camera, 720 TV Line - Analog Video Resolution
- "A" Commercial Grade LED, Auto Power & Source Recovery
- Supports Dual Voltage (24V and 12V DC)
- Built to run 24/7/365 & 3-Year Warranty




MODEL #		VZ-PVM-P1W3
FEATURES		
Screen Size	13.3"	
Max. Resolution	1080 x 1920 @60Hz	
Pixel Pitch	0.153 mm x 0.153 mm	
Brightness	250 cd/m ² (Typical)	
Contrast Ratio	800:1	
Aspect Ratio	9 : 16	
Viewing Angle (H/V)	170° / 170°	
Display Color	262 K	
Response Time	< 30 ms	
INTERFACE		
RJ 45 (TCP/IP)	2 (CMS, IP Camera)	
Camera (CVBS) Out	1	
Audio Out	1	
Micro SD In (Recording)	1	
USB In	3	
CAMERA		
Camera Type	2.1 Mega Pixel IP Camera	
Image Sensor / Encoder Chipset	SONY IMX290 / Hi3516D	
Lens	2.8 mm Fixed Lens	
Total / Effect Pixel	1080(H) x 1920p(V) 30fps	
Video Compression	H.264, MJPEG, CBR, VBR support	
Video Out	1ch CVBS (NTSC/PAL) / 1ch RJ-45 output	
Motion Detection	Support	
Network Protocol	TCP/IP, UDP, SMTP, HTTP, FTP, PPPOE, DHCP, DNS, DDNS, UPNP, RTP, RTSP	
Function	2D/3D NR, D-ZOOM, DPC, HLC/BLC, Defog, D/N, WDR, AGC, AWB	
Ethernet Port	10 / 100 Base-T	
Integration Protocol	ONVIF 2.6 (supported)	
Intelligent Detection	Perimeter, Single Virtual Fence, Loiter, Converse, Double Virtual Fences, Signal Bad	
Web Application	Windows Edge, Firefox, Chrome	

ANDROID BOARD SPEC		
Android OS	Ver. 6.1.	
CPU	RTD1295 Quad Core, ARM Cortex-A53 64bit	
RAM / Flash Memory	2GB DDR4 / 32GB	
AUDIO		
Built in speaker	3W X 2	
DIMENSIONS & WEIGHT		
Outline Dimension (W x H x D)	8.33 x 13.78 x 1.38" / 211.8 x 350.1 x 35.3 mm	
Net Weight / Gross Weight	5.4 lbs (2.45 kg) / 7.93 lbs (3.6 kg)	
MOUNT		
VESA	100 mm x 100 mm / M4 x L10 Screws	
GENERAL		
Transmitter - IR Remote Control	YES	
Power	Electrical Ratings	12V DC / 3.0 A 24V DC (AC 110V ~ 240V (w/ DC adaptor))
	Consumption	≤ 12 W
Warranty	Parts/ Labor	3 Year / 3 Year
Operating Temperature	32 ~ 122°F / 0 ~ 50°C	
Operating Humidity	5 ~ 90%RH	
Regulations	FCC(A), CE, NDA A, RoHS	
Compatible Mounts	Wall	VZ-AM02-A, VZ-SM01
	Ceiling	VZ-CM308
Compatible PoE	VZ-CSE1202	


VZ-PVM-P1B3

SMART AD PVM w/CMS Software

DIMENSION



INTERFACE



1. Micro SD Card IN
2. USB IN x 3
3. RJ 45 (Ethernet) IN
4. AUDIO OUT
5. CAMERA IP(Ethernet) OUT / P.o.E.
6. CAMERA CVBS OUT
7. DC 24V IN
8. DC 12V IN


Contact ViewZ

- Address : 1030 N ARMANDO ST., ANAHEIM, CA 92806
- Phone : (714) 996-1177, Fax : (714) 996-1138
- Sales : sales@viewzusa.com

VZ-PVM-P1W3

SMART AD PVM w/CMS Software

CONTENT MANAGEMENT SOFTWARE - FEATURE



Main Features

1. Various Source Selection

Built-in Camera , RSS, News Ticker, Live Streaming
Video, HTML, Text, Clock, Video & Image files

2. Profile Management

Display Aspect Ratio / Direction (Rotate) / Size

3. Schedule Management

Hour / Day / Week

4. Security Alert System

Display Alert Video or Image files

5. Support Media File Format

Video: AVI, MP4, MKV
Image: JPG, PNG, BMP



6. Play Log Record

Record the Content Display Time

VZ-PVM-P1W3

SMART AD PVM w/CMS Software

CONTENT MANAGEMENT SOFTWARE - SYSTEM CONFIGURATION



Powerful Remote Control

One Server Control Unlimited Smart AD PVMs

ViewZ Smart AD PVM Content Management Software(CMS) allows the administrator to control every Smart AD PVM in the organization's Intranet or Internet. From a centralized location, the signage contents that reside on a centralized server would be distributed to multiple units/locations either manually or automatically based on a set schedule

Contact ViewZ

- Address : 1030 N ARMANDO ST., ANAHEIM, CA 92806
- Phone : (714) 996-1177, Fax : (714) 996-1138
- Sales : sales@viewzusa.com